

# H03VH-H (YZwL)

## Flat twin flexible cord

Standard: ÖVE/ÖNORM E 8241 (HD 21)

### Application:

Usable under very low mechanical stress in households and office rooms for light handheld devices. Not for outdoor use, in workshops or for electric tools.



### Construction:

- 1 Copper conductor, extra-fine wire
- 2 Common insulation (PVC) over parallel conductors, easy separable



**Rated voltage:** 300/300 V



**Test voltage:** 2000 Veff



### Temperature range:

During installation: min. +5 °C  
 Operating temperature: +5 °C to +40 °C  
 Conductor temperature: max. +40 °C  
 Short circuit temperature of the conductor: max. +150 °C/5 s



**Bending radius (min.):** 5 x Ø of the cable



### Flammability:

Self extinguishing (EN 50265-2-1, IEC 60332-1)

Number of cores x nominal cross section (mm <sup>2</sup> )	Outer colours	Max. conductor resistance (Ω/km)	Outer diameter (mm) appr.	Cu-value (kg/km)	Total weight (kg/km) appr.	Standard lengths/packing (m)	Price (EUR/km)
<b>H03VH-H (YZwL)</b>							
2 x 0.5	gr, bk, wt, br	39.0	2.4 x 5.0	10	22	50 R, 100 R	291.60
2 x 0.75	gr, bk, wt, br	26.0	2.7 x 5.8	15	26	50 R, 100 R	335.61

Subject to technical changes. All figures are therefore without guarantee.